## Trimless recessed luminaire



# Simple Round A56 D68 8W 927 IP44/20 ze11006935




220-240 V





IP44 Ra >90


MAC 3











### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 1 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |
| Suction Cup        | 1 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

| Measurements: | D137x96 mm |
|---------------|------------|
| Net weight:   | 0.65 kg    |
|               |            |

Round

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 7.8 w Luminaire luminous flux\*: 472 lm Light output\*: 61.00 lm/w Colorful temperature\*: 2700 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: PRA: Mean Well APC-8-250

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com