

# Trimless recessed luminaire


Simple Longy A56 100x200 16W 930


ze11005527

220-240 V IP20 Ra >90 MAC 3



## Complectation

| | |
|---|---|
| Body | 1 |
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

| | |
|---|---|
| Measurements: | 280x180x96 mm |
| Net weight: | 2.00 kg |

| | |
|---|---|
| Rectangular | |
| Body: | Gypsum |
| Illuminant: | LED |

| | |
|---|---|
| Electrical safety class: | II |
| Degree of protection: | IP20 |
| Rated power: | 16 w |
| Luminaire luminous flux*: | 1454 lm |
| Light output*: | 91 lm/w |
| Colorful temperature*: | 3000 K |
| Color rendering index*: | Ra >90 |
| Color temperature stability*: | MAC 3 |
| cos *: | 0.55 |
| PRA: | LC 15/350/43 fixC SR SNC2 |

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP