Trimless recessed luminaire



Tetro A25 44W 840 ze11009682







P20 Ra >80


MAC 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 4 |
| Conrol gear | 4 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 475x137x70 mm |
|---------------|---------------|
| Net weight: | 2.6 kg |

Quadruple

Body: Gypsum Illuminant: LED

П Electrical safety class: IP20 Degree of protection: Rated power: 44.8 w Luminaire luminous flux*: 3770 lm Light output*: 84 lm/w Colorful temperature*: 4000 K Color rendering index*: Ra >80 Color temperature stability*: MAC 3 0.5 cos *: PRA: Mean Well APC-12-350

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

© Zenit STP zenit-stp.com

 $[\]ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.