Suspension luminaire



Liny Q RAL L200 8W 930 ze34001504








220-240 V 🚊 IP20 Ra >90


MAC 3











_	1 .	4.1
Comp	Necta	tion
\sim	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	

Body	1
LED module	1
Conrol gear	1
Ceiling attachment	1
Suspension cord	1
Cable	1

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements:	78x78x200; 78x78x65 mm
Net weight:	1.02 kg

Tube square

Body: Gypsum Illuminant: LED

Electrical safety class: 1 IP20 Degree of protection: Rated power: 7.8 w Luminaire luminous flux*: 438 lm Light output*: 56 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >90 MAC 3 Color temperature stability*: cos *: 0.4

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.

Mean Well APC-8-250

© Zenit STP zenit-stp.com

PRA:

 $[\]ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.