

# Trimless recessed luminaire


Twins Q A25 22W 930


ze11010154

220-240 V IP20 Ra >90 MAC 3



## Complectation

| | |
|---|---|
| Body | 1 |
| LED module | 2 |
| Conrol gear | 2 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

| | |
|---|---|
| Measurements: | 232x137x70 mm |
| Double | |
| Body: | Gypsum |
| Illuminant: | LED |
| Electrical safety class: | II |
| Degree of protection: | IP20 |
| Rated power: | 22.4 w |
| Luminaire luminous flux*: | 1508 lm |
| Light output*: | 69 lm/w |
| Colorful temperature*: | 3000 K |
| Color rendering index*: | Ra >90 |
| Color temperature stability*: | MAC 3 |
| cos *: | 0.5 |
| PRA: | Mean Well APC-12-350 |

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP