## Trimless recessed luminaire

# Schil

# Simple Round A56 D200 20W 930 DW ze11008507




220-240 V




IP20 Ra >90


MAC 3











### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

Measurements:	D280x96 mm
Net weight:	1.98 kg

Round

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 19.7 w Luminaire luminous flux\*: 1710 lm Light output\*: 87.00 lm/w Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.93 PRA: LC 25/350-1050/50 bDW SC PRE2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com