Trimless recessed luminaire

Schil

Simple Quadro R25 100x100 9W 930 DA ze11009199




220-240 V





IP20 Ra >90


MAC 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 200x200x70 mm |
|---------------|---------------|
| Net weight: | 1.17 kg |

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 9.3 w Luminaire luminous flux*: 767 lm 82.00 lm/w Light output*: Colorful temperature*: 3000 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.71 LCAI 15W 150mA-400mA ECO slim PRA:

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics

© Zenit STP zenit-stp.com