## Trimless recessed luminaire

## Schil


MAC 3

# Simple Quadro R25 100x100 17W 930 DA ze11005158



Ra >90








220-240 V

IP20

EHE







### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

Measurements:	200x200x70 mm
Net weight:	1.17 kg

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 17.1 w Luminaire luminous flux\*: 1443 lm 84.00 lm/w Light output\*: Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.88 LCAI 15W 150mA-400mA ECO slim PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com