## Trimless recessed luminaire

## Schil

# Simple Quadro S05 100x100 9W 930 DA ze11009219




220-240 V




IP20 Ra >90


MAC 3











### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

Measurements:	166x166x50 mm
Net weight:	0.97 kg

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 9.3 w Luminaire luminous flux\*: 804 lm 86.00 lm/w Light output\*: Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.71 LCAI 15W 150mA-400mA ECO slim PRA:

All parameters marked with \* are calculated values.

Zenith uses tried and tested components from leading suppliers.

However, it is possible for some LED technology-related faults to occur over the life of the

product.  $\begin{tabular}{ll} **- & the manufacturer reserves the right to replace the power supply with a similar one in the context of t$ 

© Zenit STP zenit-stp.com