## Trimless recessed luminaire


## Scult

MAC 3

# Twins A25 22W 830 DA









220-240 V


IP20

EHE



Ra >80





232x137x70 mm

1.49 kg

83.00 lm/w

3000 K

#### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 2 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |
| Suction Cup        | 1 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:

Net weight:

Light output\*: Colorful temperature\*:

| Double                   |         |
|--------------------------|---------|
| Body:                    | Gypsum  |
| Illuminant:              | LED     |
|                          |         |
| Electrical safety class: | II      |
| Degree of protection:    | IP20    |
| Rated power:             | 21.1 w  |
| Luminaire luminous flux* | 1749 lm |

Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.93

LCA 25W 350-1050mA one4all SC PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com