## Trimless recessed luminaire

## Schil

# Tetro A25 32W 927 DW ze11009653





220-240 V





IP20 Ra >90


MAC 3











#### Complectation

Body	1
LED module	4
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

#### $\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:	4/5x13/x/0 mm
Net weight:	2.45 kg

Quadruple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 29.1 w Luminaire luminous flux\*: 2028 lm 70 lm/w Light output\*: Colorful temperature\*: 2700 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.94 LCA 45W 500-1400mA one4all SC PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $^{**}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com