## Trimless recessed luminaire



# Tetro S05 44W 940 ze11009705




220-240 V





IP20 Ra >90


МАС 3











### Complectation

Body	1
LED module	4
Conrol gear	4
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

#### $\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

## **Specifications**

Measurements:	420x137x50 mm
Net weight:	2.08 kg
Quadruple	

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 44.8 w Luminaire luminous flux\*: 3604 lm 80 lm/w Light output\*: Colorful temperature\*: 4000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.5

PRA: Mean Well APC-12-350

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com