
## Large-size trimless recessed luminaire





# Simple MAX R50 D300 45W 940


ze11009015














#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	8
Screw x6	16
Screw self-tapping	16
Washer D5	20
Suction Cup	2
Bracket	4
Screw M5x8	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:	390x390x100 mm
Net weight:	6.91 kg
-	_
Round	
Body:	Gypsum
Illuminant:	LED
Electrical safety class:	II.
,	
Degree of protection:	IP20
Rated power:	44.5 w
Luminaire luminous flux*:	4203 lm
Light output*:	94.00 lm/w
Colorful temperature*:	4000 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
cos *:	0.95
PRA:	LC 45W 500-1400mA flexC SR EXC

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com