Large-size trimless recessed luminaire





Luno MAX C85 D300 45W 927 DA


ze11009038














Complectation

| Body | 1 |
|--------------------|----|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 8 |
| Screw x6 | 16 |
| Screw self-tapping | 16 |
| Washer D5 | 20 |
| Suction Cup | 2 |
| Bracket | 4 |
| Screw M5x8 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 490x490x123 mm |
|-------------------------------|--------------------------------------|
| Net weight: | 8.53 kg |
| Round | |
| Body: | Gypsum |
| Illuminant: | LED |
| Electrical safety class: | II |
| Degree of protection: | IP20 |
| Rated power: | 44.5 w |
| Luminaire luminous flux*: | 3498 lm |
| Light output*: | 79.00 lm/w |
| Colorful temperature*: | 2700 K |
| Color rendering index*: | Ra >90 |
| Color temperature stability*: | MAC 3 |
| cos *: | 0.96 |
| PRA: | LCA 45W 500-1400mA one4all SR PRE |

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com