## Large-size trimless recessed luminaire



MAC 3

# Luno MAX C115 D400 64W 930 DA









220-240 V


EHE



Ra >90

IP20





640x640x113 mm

### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	12
Screw x6	24
Screw self-tapping	24
Washer D5	30
Suction Cup	2
Bracket	6
Screw M5x8	6

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:

Net weight:	12.34 kg
Round Body: Illuminant:	Gypsum LED
Electrical safety class: Degree of protection: Rated power: Luminaire luminous flux*: Light output*: Colorful temperature*: Color rendering index*: Color temperature stability*: cos *: PRA:	II IP20 63.7 w 5783 lm 91.00 lm/w 3000 K Ra >90 MAC 3 0.97 LCA 60W 900-1750mA one4all SR PRE

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com