Suspension luminaire

Schil

Liny R RAL L400 8W 930 ze34001424







220-240 V




IP20 Ra >90

MAC 3







Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Ceiling attachment | 1 |
| Suspension cord | 1 |
| Cable | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | D78x400; D78x65 mm |
|---------------|--------------------|
| Net weight: | 1.43 kg |

Tube round

Body: Gypsum Illuminant: LED

Electrical safety class: Degree of protection: IP20 Rated power: 7.8 w Luminaire luminous flux*: 438 lm 56.00 lm/w Light output*: Colorful temperature*: 3000 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.4 PRA: Mean Well APC-8-250

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com