Trimless recessed luminaire

Schil

Triple Q A25 33W 830 IP44/20 DA ze11010351




220-240 V





IP44 Ra >80


MAC 3











Complectation

Body	1
LED module	3
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements: 363x137x70 mm

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 31.3 w Luminaire luminous flux*: 2624 lm 87.00 lm/w Light output*: Colorful temperature*: 3000 K Color rendering index*: Ra >80 Color temperature stability*: MAC 3 cos *: 0.96 LCA 45W 500-1400mA one4all SC PRA:

RA: LCA 45W 500-1400ITIA UNE4AIT 5

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\sp{**}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com