
## Trimless recessed luminaire





# Triple Q R25 33W 830 DW ze11010371














#### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 3 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |
| Suction Cup        | 1 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

| Measurements: | 432x167x70 mm |
|---------------|---------------|
|               |               |

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 31.3 w Luminaire luminous flux\*: 2669 lm Light output\*: 88.00 lm/w Colorful temperature\*: 3000 K Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.96 PRA: LC 45/500-1400/50 bDW SC PRE2

All parameters marked with \* are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com