

Trimless recessed luminaire



Tetro Q A25 32W 840 DA
ze11010437



220-240 V



IP20

Ra >80

MAC 3



Complectation

| | |
|--------------------|---|
| Body | 1 |
| LED module | 4 |
| Control gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements: 475x137x70 mm

Quadruple
Body: Gypsum
Illuminant: LED

Electrical safety class: II
Degree of protection: IP20
Rated power: 29.1 W
Luminaire luminous flux*: 2753 lm
Light output*: 97.00 lm/W
Colorful temperature*: 4000 K
Color rendering index*: Ra >80
Color temperature stability*: MAC 3
cos *: 0.95
PRA: LCA 45W 500-1400mA one4all SC PRE

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.