

# Surface mounted luminaire

Dyun Cut Graphite 8W 930

ze21001034

zenit



220-240 V



IP20

Ra >90

MAC 3



## Complectation

|             |   |
|-------------|---|
| Conrol gear | 1 |
| Luminaire   | 1 |

On request: painting according to the NCS scale

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

|               |           |
|---------------|-----------|
| Measurements: | D78x78 mm |
| Net weight:   | 0,4 kg    |

|             |        |
|-------------|--------|
| Tube        |        |
| Body:       | Gypsum |
| Illuminant: | LED    |

|                               |                     |
|-------------------------------|---------------------|
| Electrical safety class:      | II                  |
| Degree of protection:         | IP20                |
| Rated power:                  | 7.8 w               |
| Luminaire luminous flux*:     | 451 lm              |
| Light output*:                | 145.00 lm/w         |
| Colorful temperature*:        | 3000 K              |
| Color rendering index*:       | Ra >90              |
| Color temperature stability*: | MAC 3               |
| cos *:                        | 0.4                 |
| PRA:                          | Mean Well APC-8-250 |

All parameters marked with \* are calculated values.  
Zenith uses tried and tested components from leading suppliers.  
However, it is possible for some LED technology-related faults to occur over the life of the product.

\*\* — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.