Suspension luminaire

EVO Hang IN Black D550 78W 830 DA
ze37001141

220-240 V   ⏚   IP20   Ra >80   MAC 3

OUT

IN

Ø 550

500

38

90°   90°

200

60°   60°

300

30°   400   30°

WITH DRIVER

Ø 200

60

Complectation

LED module	1
Ceiling attachment	1
Suspension cord	4
Cable	1

IN - power supply integrated into the ceiling cup, see installation manual.

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Measurements:	D550x38; D160x25 mm
Round	
Body:	Aluminum
Illuminant:	LED
Electrical safety class:	I
Degree of protection:	IP20
Rated power:	77.3 w
Luminaire luminous flux*:	9128 lm
Light output*:	118.00 lm/w
Colorful temperature*:	3000 K
Color rendering index*:	Ra >80
Color temperature stability*:	MAC 3
cos *:	0.95
PRA:	LCA 100W 1100–2100mA one4all SR PRE

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.