## Suspension luminaire на штанге



## EVO Move IN Black D550 78W 940 ze77001125



220-240 V





IP20


Ra >90

MAC 3









## Complectation

LED module	1
Fastener	1
Ceiling attachment	1

 $\ensuremath{\mathsf{IN}}$  - power supply integrated into the ceiling cup, see installation manual.

The manufacturer reserves the right to change the configuration of the LED luminaire.

## **Specifications**

Measurements: D550x38; D160x25 mm

Round

Body: Aluminum Illuminant: LED

Electrical safety class: 1 Degree of protection: IP20 Rated power: 77.4 w Luminaire luminous flux\*: 8497 lm Light output\*: 110 lm/w Colorful temperature\*: 4000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.95 LC 100W 1100-2100mA flexC SR EXC PRA:

TVA. LC 100W 1100-2100MA MEXC SICEA

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com