
Trimless recessed luminaire


Zenit


Simple Longy A56 100x200 16W 830 IP44 ze11005531














LED

Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Illuminant:

| Measurements: | 280x180x96 mm |
|---------------|---------------|
| Net weight: | 2.11 kg |
| | |
| Rectangular | |
| Body: | Gypsum |

Electrical safety class: Ш Degree of protection: IP44 Rated power: 16 w Luminaire luminous flux*: 1686 lm Light output*: 105.00 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >80 Color temperature stability*: MAC 3 cos *: 0.55 PRA: LC 15/350/43 fixC SC SNC2

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com