
# Trimless recessed luminaire


### ×


# Simple Longy R50 100x200 16W 830 DW ze11005361




# EHI 220-240 V IP20 Ra >80 MAC 3









### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## **Specifications**

Measurements:	300x200x96 mm
Net weight:	2.31 kg

Rectangular

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 16 w Luminaire luminous flux\*: 1550 lm Light output\*: 97.00 lm/w Colorful temperature\*: 3000 K Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.97 PRA: LC 17/250-700/50 bDW SC PRE2

All parameters marked with \* are calculated values.

Zenith uses tried and tested components from leading suppliers.

However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com