Trimless recessed luminaire




MAC 3

Triple A25 24W 940









220-240 V


IP20

EHE



Ra >90





Complectation

| Body | 1 |
|--------------------|---|
| LED module | 3 |
| Conrol gear | 3 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 363x137x70 mm |
|---------------|---------------|
| Net weight: | 1.88 kg |
| | |

Triple

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 23.4 w Luminaire luminous flux*: 1785 lm Light output*: 76.00 lm/w Colorful temperature*: 4000 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.4 PRA: Mean Well APC-8-250

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com