## Suspension luminaire

### ×


MAC 3

# EVO Hang IN Black D400 64W 930 DA ze37001084





2000

220-240 V



Ra >90





### Complectation

| LED module         | 1 |
|--------------------|---|
| Ceiling attachment | 1 |
| Suspension cord    | 4 |
| Cable              | 1 |

 $\ensuremath{\mathsf{IN}}$  - power supply integrated into the ceiling cup, see installation manual.

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

| Measurements: | D400x38· D160x25 mm |
|---------------|---------------------|

IP20

Round

Body: Aluminum Illuminant: LED

Electrical safety class: 1 Degree of protection: IP20 Rated power: 63.7 w Luminaire luminous flux\*: 6243 lm Light output\*: 98.00 lm/w 3000 K Colorful temperature\*: Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 0.97 cos \*: LCA 60W 900-1750mA one4all SR PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com