
Trimless recessed luminaire





Simple Round A56 D68 11W 940 ze11006930














D137x96 mm

0.68 kg

MAC 3

Mean Well APC-12-350

Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |
| Suction Cup | 1 |

$\ \, \hbox{Dimming by TRIAC accessible on request} \\$

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Color temperature stability*:

cos *: PRA:

Measurements:

Net weight:

| Round Body: Illuminant: | Gypsum LED |
|-------------------------------|---------------|
| Electrical safety class: | II |
| Degree of protection: | IP20 |
| Rated power: | 11.2 w |
| Luminaire luminous flux*: | 759 lm |
| Light output*: | 68.00 lm/w |
| Colorful temperature*: | 4000 K |
| Color rendering index*: | Ra >90 |

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com