# Trimless recessed luminaire

## Schil

# Simple Round A56 D68 8W 927 DA ze11006955




220-240 V




IP20 Ra >90

MAC 3











### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4
Suction Cup	1

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

Measurements:	D137x96 mm
Net weight:	0.75 kg

Round

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 8.1 w Luminaire luminous flux\*: 472 lm Light output\*: 58.00 lm/w Colorful temperature\*: 2700 K Ra >90 Color rendering index\*: Color temperature stability\*: MAC 3 cos \*: 0.95 PRA: LCA 10W 150-400mA one4all SC PRE

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com