## Trimless recessed luminaire

## Schil

# Simple Quadro A56 100x100 17W 930 IP44 ze11005018




220-240 V





IP44 Ra >90


MAC 3











#### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 1 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

| Measurements: | 180x180x96 mm |
|---------------|---------------|
| Net weight:   | 1.48 kg       |
|               |               |

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 16.8 w Luminaire luminous flux\*: 1315 lm Light output\*: 78 lm/w Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.55 PRA: LC 15/350/43 fixC SC SNC2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com