## Trimless recessed luminaire

### Senit

MAC 3


# Simple Quadro A56 100x100 17W 840 DA ze11005034



Ra >80


IP20







220-240 V

EHE







#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

Measurements:	180x180x96 mm
Net weight:	1.49 kg

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 17.1 w Luminaire luminous flux\*: 1643 lm Light output\*: 96 lm/w Colorful temperature\*: 4000 K Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.88 PRA: LCAI 15W 150mA-400mA ECO slim

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com