

Trimless recessed luminaire

Simple Quadro R50 100x100 12W 940 DW
ze11005854








220-240 V



IP20

Ra >90

MAC 3



Complectation

| | |
|--------------------|---|
| Body | 1 |
| LED module | 1 |
| Control gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| | |
|---------------|---------------|
| Measurements: | 200x200x96 mm |
| Net weight: | 1.57 kg |

| | |
|-------------|--------|
| Square | |
| Body: | Gypsum |
| Illuminant: | LED |

| | |
|-------------------------------|------------------------------|
| Electrical safety class: | II |
| Degree of protection: | IP20 |
| Rated power: | 12.2 w |
| Luminaire luminous flux*: | 960 lm |
| Light output*: | 79.00 lm/w |
| Colorful temperature*: | 4000 K |
| Color rendering index*: | Ra >90 |
| Color temperature stability*: | MAC 3 |
| cos *: | 0.96 |
| PRA: | LC 17/250-700/50 bDW SC PRE2 |

All parameters marked with * are calculated values.
Zenith uses tried and tested components from leading suppliers.
However, it is possible for some LED technology-related faults to occur over the life of the product.
** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.