## Trimless recessed luminaire

## Schil

# Simple Quadro A25 100x100 9W 930 IP44 ze11009169




220-240 V




IP44 Ra >90


MAC 3











#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### Specifications

Measurements:	172x172x70 mm
Net weight:	1.19 kg

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 8.6 w Luminaire luminous flux\*: 751 lm 87.00 lm/w Light output\*: Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.51 LC 8/180/44 fixC SC SNC2 PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com