## Trimless recessed luminaire



# Simple Quadro R25 100x100 12W 930 IP44 ze11005137




220-240 V





IP44 Ra >90


MAC 3











### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 1 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

# **Specifications**

| Measurements: | 200x200x70 mm |
|---------------|---------------|
| Net weight:   | 1.16 kg       |

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 11.9 w Luminaire luminous flux\*: 1054 lm 89.00 lm/w Light output\*: Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.54 LC 10/250/40 fixC SC SNC2 PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com