## Trimless recessed luminaire

## Schil

# Simple Quadro R25 100x100 9W 840 DA ze11009197




220-240 V





IP20 Ra >80


MAC 3











### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### Specifications

Measurements:	200x200x70 mm
Net weight:	1.17 kg

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 9.3 w Luminaire luminous flux\*: 960 lm 103.00 lm/w Light output\*: Colorful temperature\*: 4000 K Color rendering index\*: Ra >80 Color temperature stability\*: MAC 3 cos \*: 0.71 LCAI 15W 150mA-400mA ECO slim PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com