## Trimless recessed luminaire

## Schil

# Simple Quadro R25 100x100 9W 927 DA ze11009198




220-240 V





IP20 Ra >90


MAC 3











### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 1 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

| Measurements: | 200x200x70 mm |
|---------------|---------------|
| Net weight:   | 1.17 kg       |

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 9.3 w Luminaire luminous flux\*: 706 lm 76.00 lm/w Light output\*: Colorful temperature\*: 2700 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.71 LCAI 15W 150mA-400mA ECO slim PRA:

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com