
Trimless recessed luminaire





EAC 220-240 V IP20 Ra >80 MAC 3 100 11/1/1 66 þr 166 171 90° 90° 200

60°

Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

Dimming by TRIAC accessible on request

© Zenit STP

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

30°

300 4ÅF

30

60°.

Measurements: Net weight:	166x166x50 mm 0.83 kg
Square Body: Illuminant:	Gypsum LED
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	8.6 w
Luminaire luminous flux*:	1005 lm
Light output*:	117.00 lm/w
Colorful temperature*:	4000 K
Color rendering index*:	Ra >80
Color temperature stability*:	MAC 3
COS *:	0.51
PRA:	LC 8/180/44 fixC SR SNC2

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

Senit