
# Trimless recessed luminaire





### EAC 220-240 V IP20 Ra >90 MAC 3 100 111111 66 Л 166 171 90° 90° 200

60°

## Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

© Zenit STP

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

30°

300 4ÅF

30

60°.

Measurements:	166x166x50 mm
Net weight:	0.83 kg
Square Body: Illuminant:	Gypsum LED
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	8.6 w
Luminaire luminous flux*:	804 Im
Light output*:	93 Im/w
Colorful temperature*:	3000 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
cos *:	0.51
PRA:	LC 8/180/44 fixC SR SNC2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

# Senit