Trimless recessed luminaire

Senit


MAC 3

Simple Quadro S05 100x100 17W 940 DW ze11005975



Ra >90








220-240 V

IP20

EHE







Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 166x166x50 mm |
|---------------|---------------|
| Net weight: | 0.92 kg |
| | |

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 16.8 w Luminaire luminous flux*: 1632 lm 97.00 lm/w Light output*: Colorful temperature*: 4000 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.97 LC 17/250-700/50 bDW SC PRE2 PRA:

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics

© Zenit STP zenit-stp.com