Trimless recessed luminaire

Schil

Simple Quadro A56 200x200 24W 830 ze11003021





220-240 V





IP20 Ra >80


MAC 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 4 |
| Screw x6 | 8 |
| Screw self-tapping | 4 |
| Washer D5 | 8 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 280x280x96 mm |
|---------------|---------------|
| Net weight: | 2.69 kg |
| | |

Square

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 23.8 w Luminaire luminous flux*: 1801 lm Light output*: 76 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >80 Color temperature stability*: MAC 3 cos *: 0.89 PRA: LCI 20W 700mA TEC SR

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com