

Trimless recessed luminaire





Simple Quadro A56 200x200 24W 830 DA ze11003121














280x280x96 mm

1801 lm

79 lm/w

3000 K

Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 4 |
| Screw x6 | 8 |
| Screw self-tapping | 4 |
| Washer D5 | 8 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Luminaire luminous flux*:

Colorful temperature*:

Light output*:

Measurements:

| Net weight: | 2.69 kg |
|---|----------------------|
| Square Body: Illuminant: | Gypsum LED |
| Electrical safety class: Degree of protection: Rated power: | II IP20 22.7 w |

Color rendering index*: Ra >80 Color temperature stability*: MAC 3 cos *: 0.95 LCA 25W 350-1050mA one4all SR PRA:

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the

 ** — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com