## Trimless recessed luminaire

## Schil

# Simple Longy A56 100x200 16W 940 ze11005529




220-240 V





IP20 Ra >90


MAC 3











#### Complectation

| Body               | 1 |
|--------------------|---|
| LED module         | 1 |
| Conrol gear        | 1 |
| Fastener           | 2 |
| Screw x6           | 4 |
| Screw self-tapping | 2 |
| Washer D5          | 4 |

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

| Measurements: | 280x180x96 mm |
|---------------|---------------|
| Net weight:   | 2.00 kg       |
|               |               |

Rectangular

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 16 w Luminaire luminous flux\*: 1570 lm Light output\*: 98.00 lm/w Colorful temperature\*: 4000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.55 PRA: LC 15/350/43 fixC SR SNC2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com