### Trimless recessed luminaire

## Senit

MAC 3

Gypsum

LED


# Simple Longy A56 100x200 23W 927 IP44 ze11005536



Ra >90


IP44







220-240 V

EHE







#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Body:

Illuminant:

Measurements:	280x180x96 mm
Net weight:	2.11 kg
Rectangular	

Electrical safety class: Ш Degree of protection: IP44 Rated power: 22.5 w Luminaire luminous flux\*: 1837 lm Light output\*: 82 lm/w Colorful temperature\*: 2700 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.94 PRA: LC 21/500/42 fixC SR ADV2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com