### Trimless recessed luminaire

## Schil

# Simple Longy R50 100x200 23W 930 IP44 ze11005578




220-240 V





IP44 Ra >90


МАС 3











#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

#### **Specifications**

Measurements:	300x200x96 mm
Net weight:	2.33 kg

Rectangular

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP44 Rated power: 22.5 w Luminaire luminous flux\*: 1835 lm 82 lm/w Light output\*: Colorful temperature\*: 3000 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.94 PRA: LC 21/500/42 fixC SR ADV2

All parameters marked with \* are calculated values.

Zenith uses tried and tested components from leading suppliers.

However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com