Trimless recessed luminaire

Senit

Simple Longy R50 100x200 23W 830 DW ze11005362








IP20 Ra >80


MAC 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | 300x200x96 mm |
|---------------|---------------|
| Net weight: | 2.31 kg |
| | |

Rectangular

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 22.7 w Luminaire luminous flux*: 2129 lm Light output*: 94 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >80 Color temperature stability*: MAC 3 cos *: 0.94 PRA: LC 25/350-1050/50 bDW SC PRE2

All parameters marked with * are calculated values.

Zenith uses tried and tested components from leading suppliers.

However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com