# Trimless recessed luminaire





#### EAC 220-240 V IP20 Ra >90 MAC 3 - 200 -11/1/ 100 172 272 ` 177 277 90° 90°

### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

## Specifications

30°

60°.

200

300 40C

30

60°

Measurements: Net weight:	272x172x70 mm 1.59 kg
Rectangular Body: Illuminant:	Gypsum LED
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	16 w
Luminaire luminous flux*:	1406 lm
Light output*:	88.00 lm/w
Colorful temperature*:	2700 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
cos *:	0.55
PRA:	LC 15/350/43 fixC SR SNC2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

