
# Trimless recessed luminaire





### EAC 220-240 V IP20 Ra >90 MAC 3 - 200 -100 200 Ċ, 300 205 305 90° 90° 200 60°. 60°

### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### Specifications

30°

300 <del>20</del>6

30

Measurements: Net weight:	300x200x70 mm 1.54 kg
Rectangular Body: Illuminant:	Gypsum LED
Electrical safety class:	11
Degree of protection:	IP20
Rated power:	22.5 w
Luminaire luminous flux*:	1974 lm
Light output*:	88.00 lm/w
Colorful temperature*:	2700 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
COS *:	0.94
PRA:	LC 21/500/42 fixC SR ADV2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

## Senit