
Trimless recessed luminaire





EAC 220-240 V IP20 Ra >90 MAC 3 - 200 -100 200 Ċ, 300 205 305 90° 90° 200 60°. 60°

Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	2
Screw x6	4
Screw self-tapping	2
Washer D5	4

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

30°

300 206

30

Measurements:	300x200x70 mm
Net weight:	1.54 kg
Rectangular Body: Illuminant:	Gypsum LED
Electrical safety class:	II
Degree of protection:	IP20
Rated power:	16 w
Luminaire luminous flux*:	1688 Im
Light output*:	106.00 Im/w
Colorful temperature*:	4000 K
Color rendering index*:	Ra >90
Color temperature stability*:	MAC 3
cos *:	0.55
PRA:	LC 15/350/43 fixC SR SNC2

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP

Senit