Trimless recessed luminaire

Schil

MAC 3

Gypsum

LED


Simple Longy S05 100x200 23W 930 IP44 ze11005698



Ra >90


IP44







220-240 V

EHE







Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

Body:

Illuminant:

| Measurements: | 266x166x50 mm |
|---------------|---------------|
| Net weight: | 1.35 kg |
| | |
| Rectangular | |

Electrical safety class: Ш Degree of protection: IP44 Rated power: 22.5 w Luminaire luminous flux*: 2237 lm Light output*: 99.00 lm/w Colorful temperature*: 3000 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3

cos *: 0.94 PRA: LC 21/500/42 fixC SR ADV2

All parameters marked with * are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com