Trimless recessed luminaire



Luno Round C50 D100 11W 927 ze11007645




220-240 V





IP20 Ra >90


MAC 3











Complectation

| Body | 1 |
|--------------------|---|
| LED module | 1 |
| Conrol gear | 1 |
| Fastener | 2 |
| Screw x6 | 4 |
| Screw self-tapping | 2 |
| Washer D5 | 4 |

Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

Specifications

| Measurements: | D290x88 mm |
|---------------|------------|
| Net weight: | 1.84 kg |
| | |

Round

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 11.1 w Luminaire luminous flux*: 846 lm Light output*: 76 lm/w Colorful temperature*: 2700 K Color rendering index*: Ra >90 Color temperature stability*: MAC 3 cos *: 0.53 PRA: LC 10/250/40 fixC SR SNC2

All parameters marked with * are calculated values.

Zenith uses tried and tested components from leading suppliers.

However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ast\ast$ — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com