## Trimless recessed luminaire

## Schil

# Luno Round C50 D200 28W 927 DW ze11008706




220-240 V





IP20 Ra >90


MAC 3











#### Complectation

Body	1
LED module	1
Conrol gear	1
Fastener	4
Screw x6	8
Screw self-tapping	4
Washer D5	8

#### Dimming by TRIAC accessible on request

The manufacturer reserves the right to change the configuration of the LED luminaire.

### **Specifications**

Measurements:	390x390x88 mm
Net weight:	4.03 kg

Round

Body: Gypsum Illuminant: LED

Electrical safety class: Ш Degree of protection: IP20 Rated power: 28.3 w Luminaire luminous flux\*: 2203 lm Light output\*: 78 lm/w Colorful temperature\*: 2700 K Color rendering index\*: Ra >90 Color temperature stability\*: MAC 3 cos \*: 0.93 PRA: LC 45/500-1400/50 bDW SC PRE2

All parameters marked with \* are calculated values. Zenith uses tried and tested components from leading suppliers. However, it is possible for some LED technology-related faults to occur over the life of the product.

 $\ensuremath{^{**}}$  — the manufacturer reserves the right to replace the power supply with a similar one with the same characteristics.

© Zenit STP zenit-stp.com